

| | |
|---------------|-------|
| Project Name: | |
| Location: | |
| Item: | Qty.: |
| Model: | |

Reach-In Refrigeration



Model MXCR-23FD/MXCF-23FD



Model MXCR-49FD/MXCF-49FD



Model MXCR-72FD/MXCF-72FD

FEATURES

- Stainless steel exterior and coated aluminum interior ensures years of long life and maximum durability
- Internal storage capacity is 49 cu. ft
- CFC-free polyurethane foam insulation
- (3) heavy-duty, adjustable, PE coated wire shelves per section
- Door locks and swivel casters come standard
- Utilizes environmentally friendly CFC-free refrigerant, Refrigerator R134A / Freezer R404A
- Automatic defrost system
- Digitally controlled temperature system maintains optimum temperature and LED display is easily viewed from exterior
- Holding temperature: Refrigerator 28°F to 39°F Freezer 5°F to -9.4°F
- Large evaporator and condenser for quick cooling and greater efficiency
- Horsepower: Refrigerator - 1/3 HP Freezer 3/4 HP
- Automatic interior lighting
- Self contained system
- Recessed handles
- 15 amp plug



Specifications subject to change without notice.

Approvals: UL, UL Sanitation

Reach-In Refrigeration

Model MXCR-23FD/ MXCF-23FD

Model MXCR-49FD/MXCF-49FD

Model MXCR-72FD/MXCF-72FD



Maxx Cold reach-in refrigeration is built to last. Temperature is digitally controlled and easily viewed from the exterior of the cabinet. Stainless steel construction ensures years of long life and maximum durability. Maxx Cold units are designed with energy savings in mind.

Dimensional Data

| Model | Dim (WxDxH") | Capacity | Hp | Temp | Watts | Doors | Weight | Shelves | NEMA Plug (115/60/1 Only) |
|---------------------------|--|----------|-------|----------------|-------|-------|--------------------|---------|------------------------------|
| MXCR-23FD Refrigerator | 26.75 x 31 x 82.75 (679x787x2120mm) | 23 Cu Ft | 1/3 | 28° to 39°F | 690 | 1 | 271 LB 123 KG | 3 | 5-15P |
| MXCF-23FD Freezer | 26.75 x 31 x 82.75 (679x787x2102mm) | 23 Cu Ft | 1/3 | -9° to 5° F | 1035 | 1 | 284 LB 129 KG | 3 | 5-15P |
| MXCR-49FD Refrigerator | 54 x 31 x 82.75 (1372x787x2102mm) | 49 Cu Ft | 1/3 | 28° to 39°F | 1035 | 2 | 397 LB 180 KG | 6 | 5-15P |
| MXCF-49FD Freezer | 54 x 31 x 82.75 (1372x787x2102mm) | 49 Cu Ft | 3/4 | -9° to 5° F | 1380 | 2 | 403 LB 182.8 KG | 6 | 5-15P |
| MXCR-72FD Refrigerator | 81.0x32.75x82.75 (2057x831x2102mm) | 72 Cu Ft | 3/4 | 28° to 39°F | 1150 | 3 | 669 LB 303 KG | 9 | 5-15P |
| MXCF-72FD Freezer | 81.0x32.75x82.75 (2057x831x2102mm) | 72 Cu Ft | 1 1/4 | -9° to 5° F | 1840 | 3 | 776 LB 351 KG | 9 | 5-15P |